

The professionals for renovation and modernization.

**FLEX**  
Das Original






# LD 15-10 125

Grinding machine for dust-free grinding



- Electronic control: with tachogenerator constant speed control, soft start, overload protection and temperature monitoring
- Dust extraction: prevents dust nuisance, reduces disc wear, keeps the concrete pores open for the new coating
- Reliable 1450 watt high-performance motor with sufficient power reserves
- Flexible rubber vacuum ring with low-wear metal ring: moves smoothly over the surface and protects against dust and flying stones
- Vacuum guard: with stepless height adjustment
- With steplessly adjustable, vibration-proof, ergonomic auxiliary handle, for optimum handling and machine control
- For fixed hose connection. Adapter with FLEX Clip connection for Ø 32 mm snap connection included in the standard equipment.
- Recessed spindle lock, to avoid unintentional activation
- Ideally suited for processing walls, ceilings and floors. Efficient and economic working thanks to optimum coordination between machine and sanding disc

## Kit System

	LD 15-10 125 kits	Order no.
	Turbo-Jet kit	405.914
	Thermo-Jet Plus kit	405.930
	Screed-JetPlus kit	405.957
	PCD grinding disc kit	405.973
	PKD-Jet 5-Cut kit	406.007

LD 15-10 125	
Disc-Ø	125 mm
No load speed	10000rpm
Power input	1450 watt
Power output	950 watt
Vibration dose value VDV	< 6,4 m/s <sup>2</sup>
Tool fixture	M 14
Weight	3.2 kg



08-2013 / Price and technical specifications are subject to change without prior notice. FLEX accepts no responsibility for mistakes and printing errors.

Perfect up to the edge.

**FLEX**  
Das Original

# LD 15-10 125 R

## Grinding machine for dust-free grinding close to edges



New handle

Robust H07RN-F cable






- Electronic control: with tachogenerator constant speed control, soft start, overload protection and temperature monitoring
- Dust extraction: prevents dust nuisance, reduces disc wear, keeps the concrete pores open for the new coating
- Reliable 1450 watt high-performance motor with sufficient power reserves
- Guard with pivoting segment to allow grinding right up to the wall. Height-adjustable to the disc height and for optimum dust extraction
- With steplessly adjustable, vibration-proof, ergonomic auxiliary handle, for optimum handling and machine control
- For fixed hose connection. Adapter with FLEX Clip connection for Ø 32 mm snap connection included in the standard equipment.
- Recessed spindle lock, to avoid unintentional activation
- Ideally suited for processing walls, ceilings and floors. Efficient and economic working thanks to optimum coordination between machine and sanding disc



Guard can be open without any tools. Ideal for working on the edge.

### Kit System

LD 15-10 125 R	
Disc-Ø	125 mm
No load speed	10000 rpm
Power input	1450 watt
Power output	950 watt
Vibration dose value VDV	< 6,4 m/s <sup>2</sup>
Tool fixture	M 14
Weight	2.9 kg

	LD 15-10 125 R kits	Order no.
	Turbo-Jet kit	405.906
	Thermo-Jet Plus kit	405.922
	Estrich-Jet Plus kit	405.949
	PKD-Jet kit	405.965
	PKD-Jet 5-Cut kit	405.981

Your FLEX dealer